From a design team with over 75 years of award winning industry experience: an affordable, full featured, mid-size, rugged and lightweight remote head. Designed for HD, film & broadcast camera systems.

THE TALON

by RAVENSCLAW Inc.

- 210 degrees per sec. w/ 35lb camera
- Full slip-rings for continuous 360° motion
- Virtual set capable, multiple configurations
- · Easily configured for over or under-slung
- Manufactured and assembled in the U.S.A.

Height 19.5 inches Width 12 inches Depth 6 inches Weight 21 pounds

Camera synchronization

Max camera weight 35 pounds Programmable soft travel limits

Rigid
Precise
Repeatable
Accurate
Quiet

Standard Features:

Record and move to up to 2000 marked positions
Record and playback up to 1 hour and up to 2000 takes
Programmable maximum speeds for each axis
Programmable smoothing for each axis
Precise homing via operator command
Up to 2500 feet between controller and head
Programmable motion limits
Servo tuning from remote console
Fujinon and Canon serial lens control

Extremely rigid with precise smooth motion for long lenses
Joystick wheel control for Pan, Tilt and Zoom; knob control for Focus
Share recorded data with laptop: streaming and upload & download



full function remote with hand wheel option

Optional Features:

Direct connection (head to KuperNode for motion control & virtual set applications) Motion capture package for additional recorded axes

Preston lens control interface allowing recording and playback

Encoded pan bar interface
Encoded hand wheel interface

Intervalometer operation
Custom lens control interfaces
Water tight shipping case

Standard package:

Two axis Talon remote head Talon remote controller Remote head power cable - 30 ft. Control cable - 50 ft.

Ravensclaw Inc. PO Box 657

Ashland, OR 97520

Voice: 541 488 5271 Fax: 541 488 5526